

RD-606i 5.1CH NETWORK AV RECEIVER



5.1 Channel Network AV Receiver with Internet Radio

SPECIFICATIONS

Amplifier	
Power Output - Stereo	100W x 2 (40Hz ~ 20kHz, THD 0.7%) @ 6 Ohm
Power Output - Surround	100W x 5 (1kHz, THD 0.7%) @ 6 Ohm / One Channel Driven
THD	0.05%
Input Sensitivity/Impedance	250mv Line (CD, Tape, Video @ 47k Ohm)
S/N Ratio	95dB (CD, Tape, Video)
Tone Controls	Bass (100Hz) +/- 10dB Treble (10kHz) +/- 10dB
Frequency Response	Line (CD, Tape, Video) 20Hz -50kHz +0dB, -3dB
FM Tuner	
Frequency Range	87.5-108.0MHz
RDS Function	RDS, PTY, TP Search PS, RT, CT
Usable Sensitivity (Mono)	12.8dBf
46dB Quieting Sensitivity	Mono 20.2dBf Stereo 45.3dBf
S/N Ratio (65dBf)	Mono 55dB Stereo 50dB
THD (65dBf, 1kHz)	Mono 0.5% Stereo 1.0%
Frequency Response	30Hz-12kHz, +/- 3.0dB
Stereo Separation	1kHz, 35dB
IF Rejection Ratio	80dB

AM Tuner	
Frequency Range	522-1611kHz
Usable Sensitivity	500uV/m
THD	400Hz, 30% Modulation, 0.4%
S/N Ratio	40dB
Selectivity	25dB
Video	
Input Sensitivity	75 Ohm, 1Vp-p
Output Level	75 Ohm, VCR/Monitor Out, Composite, 1Vp-p
Frequency Response	Composite Video/S-Video, 10Hz-10MHz (/- 2dB)
Crosstalk	50db (1MHz)
General	
Dimensions (W x H x D)	435 x 143 x 359mm
Weight	8.9kg

*Specifications are subject to change and or improvement without notice.