

## RX-4109 STEREO RECEIVER



Remote Controlled Stereo Receiver with Phono Input

### SPECIFICATIONS

Amplifier	
Power Output - Stereo	100W x 2 (20Hz-20kHz, THD 0.03%) @ 6 Ohm
THD	0.09%
Input Sensitivity/Impedance	200mv Line (CD, Tape, Video @ 47k Ohm)
S/N Ratio	95dB
Tone Controls	Bass (100Hz) /- 10dB Treble (100Hz) /- 10dB
Frequency Response	Line (CD, Tape, Video) 20-44kHz, /-3dB
FM Tuner	
Frequency Range	87.5-108.0MHz
RDS Function	RDS, PTY, TP Search PS, RT, CT
Usable Sensitivity (Mono)	17.2dBf
46dB Quieting Sensitivity	Mono 20.8dBf Stereo 41.2dBf
S/N Ratio (65dBf)	Mono 72dB Stereo 65dB
THD (65dBf, 1kHz)	Mono 0.5% Stereo 0.4%
Frequency Response	20Hz-15kHz, /- 1.0dB
Stereo Separation	1kHz,45dB
AM Suppression Ratio	45dBf, 60dB
Channel Sensitivity	98MHz, /-400kHz, 65dB
Image Rejection Ratio	-
IF Rejection Ratio	120dB
Spurious Rejection Ratio	80dB

AM Tuner	
Frequency Range	520-1710kHz
Usable Sensitivity	400uV/m, 500uV
THD	400Hz, 30% Modulation, 0.01%
S/N Ratio	40dB
Frequency Response	-
Image Rejection Ratio	-
Selectivity	25db
General	
Dimensions (W x H x D)	435 x 138 x 332mm
Weight	8.8kg

\*Specifications are subject to change and or improvement without notice.